



## Automatic tilt back tyre changer with dual assist arm for car wheels 10" – 24"

Automatic tilt back tyre changer with dual assist pneumatic helper arm for easy operation on low profiled tyres. Robust and convenient, reinforced chassis, air operated tilt-back tower, bead breaker double effect cylinder d.200 mm., made in aluminum, clamping capacity 10"-24".

### Description

Traditional automatic "Budget line" tyre changer, robust and convenient, equipped with multi-assist helper arm, air operated tilt-back tower, turntable clamping capacity 10"-24" and powerful bead breaker cylinder. Special designed fitting head (provides great versatility and performance for even low profiled tyres).

### Functions

- Tilting tower, sliding horizontal arm with  $\varnothing$  41 mm operating arm;
- Bead breaker double effect cylinder  $\varnothing$  200 mm., made in aluminum;
- Reinforced chassis;
- Tabletop thickness 12 mm;
- Fitting head designed for both standard and low profiled tyre applications;
- CE inflating gauge (standard);
- Equipped with pedal (assist) (standard);
- Suitable for Tubeless tyre bead seating system (optional).

### SILVERLINE

The best choice for the average tyre shop with budget goal.

### Giuliano Industrial S.p.A.

## Standard Features

---

External clamping range	10" - 22" By adjustable jaws
Internal clamping range	12" - 24" By adjustable jaws
Max. tyre diameter	1010 mm (39")
Max. tyre width	390 mm (15")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 psi)
Balancing speed	7-14 rpm
Power supply	400V - 3ph - 2 speed 220V - 1ph
Motor power	0,75 / 1,125 kW (3 ph) 0,9 kW (1 ph)
Air Inflation Pressure	3,5 bar (50 Psi)
Net weight	300 Kg
Dimensions (WxDxH)	1420 x 1740 x 2010 mm



Standard accessories



**HP4** (9246608)

HP4 additional double arm to ease mounting operations of low profiled and UHP tyres.

**Not** available for:

- Maxi Pro Series machines
- S 116
- S 116 Bike



**G-CLAMP** (9217471)  
G-CLAMP Set. Helps adding extra bead-pressure points on top bead while assembling it. Kit includes 2 regular and 2 extra-size G-clamps.



**RJP** (9236282)  
Kit of rubber coated jaw protectors.



**T1** (9217472)  
Kit of 4 rubber protections for steel rims.



**T2** (9217473)  
Kit of 4 rubber protections for aluminium rims.



**T3** (9217474)  
Kit of 4 rubber protectors for aluminium rims with arched spokes.



**LB** (9216805)  
Lube paste bucket, 5 kg.



**GUN 1** (9236658)  
Tubeless inflation external kit.



**ORJP** (9216166)  
Kit of rubber protections for clamping rims from inside using conventional jaws.



**MOTO-AD** (9235081)  
Kit of 4 motorcycles adaptors with wider clamps, standard height. Suitable for any kind of car tyre changers turntable in GIULIANO range, allows easy clamping of motorcycle and scooter wheels from 6" to 23", when mounted on standard jaws.



**ATV-AD** (9235082)  
Kit of 4 clamping adaptors for HARLEY DAVIDSON wheels, oversize height, 6" - 24", with screw lock.



**QCK** (9208996)  
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tyre-changer).



**SHS** (9209086)  
Mounting/demounting tool for soft tyres on steel wheels, including hub for connection to quick release kit (**QCK**)



**AHS** (9213611)  
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



**EHS** (9235009)  
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



**QX** (9243338)  
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force....**



**QXHS** (9230814)  
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



**PAD** (9237711)  
Manual bead depressor with extendable travelling pad.



**QCK** (9208996)  
Quick release kit for mounting tools (includes one plastic tool and one hub for connecting the tool delivered with the tyre-changer).



**SHS** (9209086)  
Mounting/demounting tool for soft tyres on steel wheels, including hub for connection to quick release kit (**QCK**)



**AHS** (9213611)  
Mounting/demounting tool for arched spokes rims, including hub for connection to quick release kit (**QCK**).



**EHS** (9235009)  
Mounting/demounting tool for iron wheels with projecting central hub, including hub for connection to quick release kit (**QCK**)



**QX** (9243338)  
QX is a leverless mount/demount device, suitable for conventional, UHP and Run Flat tyres. Exclusive GIULIANO **Patent**, it works in the same exact way of your traditional tyre bar, but **without operator's manual force....**



**QXHS** (9230814)  
Kit of **QX** adaptors for connection to quick release kit (**QCK**).



**HD** (9208633)  
Manual bead depressor.



**PAD** (9237711)  
Manual bead depressor with extendable travelling pad.



**WL 6** (9242824)  
Pneumatic wheel lifter for passenger car type changers with foot control for the ascent and descent of the wheel. Pneumatic wheel lifter for car tyre changer: facilitates the positioning of the wheel on the tyre changer. Foot control for the ascent...



**QX-AD** (9232767)  
**QX, QX Plus** adjusting tool and **LeverNoLever** System



**TPP 4** (9234452)  
Kit of 10 rear plastic protections, for **QX, QX Plus** and **LeverNoLever** System



**TPP 5** (9234453)  
Kit of 10 front plastic protections, for **QX, QX Plus** and **LeverNoLever** System



**CPC** (9214251)  
Pressing cone for clamping RUN FLAT tires from outside.



Scan QR code to go to product web page



**Giuliano Industrial S.p.A.**

via Guerrieri 6

Correggio (RE)

Italy

+39 0522 731111

+39 0522 633198

<https://www.giuliano-automotive.com>



**Social Network**



Facebook



YouTube



Twitter



[www.giuliano-automotive.com](http://www.giuliano-automotive.com)